

LESS IS BEST

Less of the problems you don't need

Less Tripping Less Sensitivity

- Improved electronic circuitry
- Will not trip due to high voltages on the neutral wire

Less Hassle

- No polarity for supply connections
- Able to exit service bypass mode without turning off power

Less burn-outs

- Higher temperature construction
- Reformulated potting compound and higher grade components

Less troubleshooting

- Simple LED/service bypass mode diagnostics
- Quick, two step procedure determines if the fault is in the secondary or ground circuit

Less service models

- With the 25mA self-regulating models, service inventories can be reduced to just two model numbers in each series



The New
Guardian II



Neon Transformers

06/03



LED Lighting Systems



SIGN PRODUCTS GROUP

815.675.6641 www.actown.com

800.531.6366 HOTLINE

815.675.2050 FAX

Electronic Ballasts

Standard Outdoor Transformers

CATALOG NUMBER	SECONDARY		PRIMARY VA	INPUT AMPS		WEIGHT (lbs)
	Volts	mA		120V	277V	
15030-OG	15,000	30	450	3.9	1.7	27
15025-OG	9,000-15,000	25	375	2.9	N/A	27
12030-OG	12,000	30	360	3.2	1.2	26
10530-OG	10,500	30	315	2.9	1.2	26
9030-OG	9,000	30	270	2.4	0.9	14.5
9025-OG	3,000-9,000	25	225	1.6	N/A	14.5
7530-OG	7,500	30	225	2	0.7	13.5
15060-OG	15,000	60	900	6.8	2.9	42
12060-OG	12,000	60	720	5.5	2.4	41
9060-OG	9,000	60	540	4.7	1.7	31
7560-OG	7,500	60	450	3.9	1.5	24
6060-OG	6,000	60	360	3.2	1.2	23
5060-OG	5,000	60	300	2.6	1	21
4060-OG	4,000	60	240	2.1	0.9	12
3060-OG	3,000	60	180	1.6	0.6	11

Versamount™ Fully Enclosed Transformers

CATALOG NUMBER	SECONDARY		PRIMARY VA	INPUT AMPS		WEIGHT (lbs)
	Volts	mA		120V	277V	
15030-VMG	15,000	30	450	3.9	1.7	29
15025-VMG	9,000-15,000	25	375	2.9	N/A	29
12030-VMG	12,000	30	360	3.2	1.2	27
10530-VMG	10,500	30	315	2.9	1.2	27
9030-VMG	9,000	30	270	2.4	0.9	15
9025-VMG	3,000-9,000	25	225	1.6	N/A	15
7530-VMG	7,500	30	225	2	0.7	14
15060-VMG	15,000	60	900	6.8	2.9	44
12060-VMG	12,000	60	720	5.5	2.4	38
9060-VMG	9,000	60	540	4.7	1.7	32
7560-VMG	7,500	60	450	3.9	1.5	29
6060-VMG	6,000	60	360	3.2	1.2	27
5060-VMG	5,000	60	300	2.6	1	16
4060-VMG	4,000	60	240	2.1	0.9	15
3060-VMG	3,000	60	180	1.6	0.6	14

Self-regulating Transformers ■ Intended to reduce service truck inventory

- Choked to draw 25mA maximum
- Designed to operate at full current
- Cannot be overloaded
- Reduce inventory
- Simplify field replacement



All transformers listed have a mid-point return wiring option and are UL 2161 Listed.